



221 E. Carolina Avenue Memphis, TN 38126  
(800) 424-9300 CHEMTREC  
INFORMATION TELEPHONE NO.: (901) 526-2211  
www.farrell-calhoun.com help@farrell-calhoun.com

## PRODUCT DATA SHEET



# WOOD KRAFT WATERBORNE PENETRATING WIPING STAINS

### DESCRIPTION

Wood Kraft Waterborne Penetrating Wiping Stains (#1500 Clear Base and #1512-#1517 line standard colors) are premium pigmented oil modified, alkyd, waterborne dispersion wiping stains formulated to provide quality results with a minimum of work. These stains develop the natural beauty of both hard and soft woods without obscuring grain patterns with minimal grain raising. The quick drying, penetrating action allows complete staining and finish coating of wood surfaces in a single day. These stains are designed to be coated with a protective coat of polyurethane or lacquer finish when thoroughly dry.

### TYPICAL USE

Wood Kraft Waterborne Penetrating Wiping Stains are recommended on properly prepared interior bare wood surfaces such as doors, cabinets, woodwork, paneling, and new furniture. These products may also be used on exterior bare wood surfaces such as doors and patio furniture. Not recommended for use on large areas of wood siding, wood decks, or exterior wood trim.

### SURFACE PREPARATION

The surface to be stained should be dry and free of any dirt, grease, wax, fingerprints, pencil marks or other foreign contaminants. Any small holes or surface imperfections should be filled with wood filler and sanded to a smooth finish, followed by dusting. Always sand, in the direction of the wood grain. Raw wood surfaces that vary in porosity or tone should be sealed with a pretreatment conditioner to produce a uniform base for staining. If you have any questions about proper surface preparation check your surface preparation guide or consult your Farrell-Calhoun representative.

### COLOR

Available in 5 standard colors, and a clear base (#1500), that can be tinted with universal colorants to wide range of colors.

### SPECIFICATIONS

**Finish:** Flat @ 60° 2.0 – 3.0

**Solids:** 32.0% by weight/30.0% by volume ±2%

**Weight/Gallon:** 8.5 +/- 0.1 Pounds

**Flash Point:** > 150°F

### ENVIRONMENTAL

**VOC:** 125 grams per liter; 1.04 lb/gal

LEED v3.0 Compliant

SCAQMD Rule 1113 (2006) Compliant

OTC Compliant (2003)

### RECOMMENDED SPREAD RATE

Approximately 500 square feet per gallon, but coverage figures will vary greatly with texture and porosity of the wood surface.

### DRY TIME

At 77°F and 50% relative humidity: Thirty minutes to dust, dirt and bug free, one to two hours to tack free, and four to eight hours to recoat.

### APPLICATION PRECAUTIONS

**CAUTION! Used cloths must be spread out to dry!** The cloths must then be put in a sealed steel container. Failure to do so could result in a fire which is caused by spontaneous combustion. This can occur when cloths are piled up and not spread out to dry, or not put in a sealed steel container.

### APPLICATION EQUIPMENT

This product is designed to be sprayed with conventional air, brushed with a quality white bristle brush or wiped with a clean dry knit cloth, then have the excess stain wiped off with a clean cloth.

### THINNING

Do not thin. Use at full strength

### CLEAN-UP

Warm, Soapy Water

### PACKAGING

1 Gallon Cans and 1 Quart Cans

**STORAGE TEMPERATURE**

Minimum 35°F Maximum 90°F

**SHELF LIFE**

12 months at recommended storage temperature when stored in tightly sealed containers.

*The technical data contained in this data sheet is accurate to the best of our knowledge. No warranty is expressed or implied since the method of application and its intended use is beyond our control.*