



221 E. Carolina Avenue Memphis, TN 38126  
(800) 424-9300 CHEMTREC  
INFORMATION TELEPHONE NO.: (901) 526-2211  
www.farrell-calhoun.com help@farrell-calhoun.com

## PRODUCT DATA SHEET

# 475 PERFIK-KOTE INTERIOR VINYL-ACRYLIC HIGH BUILD LATEX PRIMER/SEALER

### PRODUCT PROFILE

#### DESCRIPTION

475 Perfik-Kote is a high solids vinyl-acrylic latex coating that is designed for use as a primer/sealer on wallboard surfaces. Unlike most wall primers, #475 goes on in a heavy bodied film which makes it sand exceptionally well, as well as allow it to minimize surface imperfections and irregularities. #475 has good sealing properties and enamel hold-out. #475 is high hiding, fast drying, low odor, low VOC, and dries to a flat finish. Use of this product will not only provide an excellent surface for the topcoat to adhere to, but will also insure good coverage of the next coat of paint. This product may be top coated with either latex or oil-based products.

#### TYPICAL USE

475 Perfik-Kote is highly recommended as a primer/sealer for interior plaster and wallboard surfaces. This product is not recommended for priming bleeding woods metal surfaces, or glossy enamel surfaces.

#### SURFACE PREPARATION

The surface to be painted should be dry and free of any dirt, chalk, loose or peeling paint, grease, mildew, oil, rust, or other foreign contaminants. Repair/Caulk all cracks and fill all small holes or surface voids with putty or spackling compound and then sand to smooth finish followed by dusting. If you have any questions about proper surface preparation check your surface preparation guide or consult your Farrell-Calhoun representative.

#### COLOR

Available in white and can be tinted to any pastel color with universal colorants.

#### FINISH

Flat @ 60° 1.9 – 2.4

#### SOLIDS

60.0% by weight/40.4% by volume

#### THEORETICAL APPLICATION RATE

648 square feet per gallon at 1.0 mil dry film thickness. Coverage figures do not include loss of material while mixing, porosity or irregularity of the surface to be painted, or application methods.

**RECOMMENDED  
SPREAD RATE**

To minimize surface imperfections it is recommended that #475 be applied with a long nap roller cover at a rate of 150 square feet per gallon. On smooth surfaces this product may be applied at 300 square feet per gallon to achieve a WFT of 10.7 to 5.3 Mils and a DFT of 4.6 to 2.3 Mils per coat.

**VOC**

26 grams per liter.

**DRY TIME**

At 77°F and 50% relative humidity: Thirty minutes to dust, dirt and bug free, one hour to tack free, and two to four hours to recoat.

**APPLICATION  
EQUIPMENT**

Airless spray, synthetic brush or roller cover. If an airless sprayer unit is used a .021 tip size and a 1.00 gallons per minute pump are recommended.

**THINNING**

Thinning is not recommended. If thinning is required for spray applications, thin with clean tap water at a rate of 1/2 pint (8 ounces) of clean tap water to one gallon of paint.

**CLEAN-UP**

Warm, soapy water.

---

**SHIPPING & STORAGE**

---

**PACKAGING**

5 Gallon Pails.

**WEIGHT/GALLON**

12.7 +/-0.1 Pounds

**STORAGE  
TEMPERATURE**

Minimum 35°F. Maximum 90°F.

**SHELF LIFE**

12 months at recommended storage temperature when stored in tightly sealed containers.

*The technical data contained in this data sheet is accurate to the best of our knowledge. No warranty is expressed or implied since the method of application and its intended use is beyond our control.*