



221 E. Carolina Avenue Memphis, TN 38126
(800) 424-9300 CHEMTREC
INFORMATION TELEPHONE NO.: (901) 526-2211
www.farrell-calhoun.com help@farrell-calhoun.com

PRODUCT DATA SHEET

479 HIGH BUILD EASY PRIME SHEETROCK PRIMER

PRODUCT PROFILE

DESCRIPTION

#479 Easy Prime is a high build vinyl-acrylic latex coating that is designed for use as a primer/sealer on wallboard surfaces. Unlike most wall primers, #479 goes on in a heavy bodied film which makes it sand exceptionally well, as well as allows it to minimize surface imperfections and irregularities. If severe irregularities are present, use #475 Perfik-Kote. #479 has good sealing properties and enamel hold-out. #479 is high hiding, fast drying, low odor, low VOC, and dries to a flat finish. Use of this product will not only provide an excellent surface for the topcoat to adhere to, but will also insure good coverage of the next coat of paint. This product may be top coated with either latex or oil-based products.

TYPICAL USE

#479 Easy Prime is highly recommended as a primer/sealer for interior plaster and wallboard surfaces. This product is not recommended for priming bleeding woods, metal surfaces, or glossy enamel surfaces.

SURFACE PREPARATION

The surface to be painted should be dry and free of any dirt, chalk, loose or peeling paint, grease, mildew, oil, rust, or other foreign contaminants. Repair/Caulk all cracks and fill all small holes or surface voids with putty or spackling compound and then sand to smooth finish followed by dusting. If you have any questions about proper surface preparation check your surface preparation guide or consult your Farrell-Calhoun representative.

COLOR

Available in white and can be tinted to any pastel color with universal colorants.

FINISH

Flat @ 60 Degrees 2.0 to 2.5

SOLIDS

50.0% by weight/29.6% by volume

THEORETICAL APPLICATION RATE

455 square feet per gallon at 1.0 mil dry film thickness. Coverage figures do not include loss of material while mixing, porosity or irregularity of the surface to be painted, or application methods.

RECOMMENDED SPREAD RATE

To minimize surface imperfections it is recommended that #479 be applied with a long nap roller cover at a rate of 150 square feet per gallon. On smooth surfaces this product may be applied at 300 square feet per gallon.

VOC	25 grams per liter.
DRY TIME	At 77°F and 50% relative humidity: Thirty minutes to dust, dirt and bug free, one hour to tack free, and two to four hours to recoat.
APPLICATION EQUIPMENT	Airless spray, synthetic brush or roller cover. If an airless sprayer unit is used, a .017 to .019 tip size is recommended.
THINNING	Thinning is not recommended. If thinning is required for spray applications, thin with clean tap water at a rate of 1/2 pint (8 ounces) of clean tap water to one gallon of paint.
CLEAN-UP	Warm, soapy water

SHIPPING & STORAGE

PACKAGING	5 Gallon Pails
WEIGHT/GALLON	11.5 +/- 0.1 Pounds
STORAGE TEMPERATURE	Minimum 35°F. Maximum 90°F.

The technical data contained in this data sheet is accurate to the best of our knowledge. No warranty is expressed or implied since the method of application and its intended use is beyond our control.